

GERHARD HUTH, citizen of Germany, whose residence and post office addresses are Am Geisberg 6, 97618 Leutershausen, Germany, has invented certain new and useful improvements in a

PERMANENT MAGNET SYNCHRONOUS MOTOR

of which the following is a complete specification:

0970997-120600

PERMANENT MAGNET SYNCHRONOUS MOTOR

CROSS-REFERENCES TO RELATED APPLICATIONS

[0001] This application claims the priority of German Patent Application Serial No. 199 58 682.9, filed December 6, 1999, the subject matter of which is incorporated herein by reference.

BACKGROUND OF THE INVENTION

[0002] The present invention relates to a permanent magnet synchronous motor, and more particularly to a 4-pole motor.

[0003] High-speed permanent magnet synchronous motors have typically four poles as determined by the maximum voltage converter frequency. The running concentricity of a synchronous motor, in particular of the motor spindle, has to be very high, requiring suitable measures for suppressing torque ripple. This in turn typically requires a relatively complex winding system with the following parameters:

[0004] Number of slots in the stator $N = 36$.

Number of poles $2p = 4$.

Pitch factor $w/\tau = 7/9$.

Skew angle of the stator $\gamma = 10^\circ$.

SUMMARY OF THE INVENTION

[0005] It is thus an object of the present invention to provide an improved permanent magnet synchronous motor, obviating the afore-stated drawbacks.

[0006] In particular, it is an object of the present invention to provide an improved permanent magnet synchronous motor with a winding system which generates electromagnetic effects similar to those of a winding system of a conventional permanent magnet synchronous motor while yet can be manufactured in a more simple manner.

[0007] These objects, and others which will become apparent hereinafter, are attained in accordance with the present invention by providing a stator and a permanent magnet excited rotor, wherein the stator has a winding with cyclically repeating winding factors $|\xi_p| = 0.945$, $|\xi_{5p}| = 0.140$ and $|\xi_{7p}| = 0.060$, and a skew angle $\gamma = \frac{2\pi}{18p}$, wherein p is the number of pole pairs.

[0008] In a configuration of the stator with a slot number N = 18 slots, the winding is formed as a single layer winding, wherein the three winding factors repeat cyclically. The optimal skew angle is $\gamma = \frac{2\pi}{18p}$.

[0009] There is also the option to reduce the slot number of the stator by one half, so that only $N = 9$ slots are provided in the stator. In this case, the winding is a special two-layer winding. Again, three possible winding factors exist which are identical to those of the afore-described winding system with $N = 18$ slots. The optimal skew angle of the stator in this case is also $\gamma = \frac{2\pi}{18p}$.

[0010] The winding arrangement disclosed in the present invention is particularly suited for small-size, high-speed four pole synchronous spindles. This winding arrangement in conjunction with a mutual skew between the rotor and the stator optimally suppresses torque ripple. Slot latching is therefore encountered only as of the fourth slot harmonic. The term "slot latching" will denote a physical effect in which latching torque is effective in particular at standstill and during starting. A reduction of latching torque can be realized, e.g., by skewing the slot.

BRIEF DESCRIPTION OF THE DRAWING

[0011] The above and other objects, features and advantages of the present invention will be more readily apparent upon reading the following description of a preferred exemplified embodiment of the invention with reference to the accompanying drawing, in which:

generator is concerned and a sinusoidal rotary field when a motor is concerned.

[0021] The above winding factors repeat cyclically. Windings of this type are suitable for both rotary motors and linear motors. The optimum skew angle in this case is $\gamma = \frac{2\pi}{18p}$, wherein p is the number of pole pairs.

[0022] In the layout of the single layer stator winding of FIG. 1 with the slot number N = 18 slots, an X indicates the direction of the current in the winding 20 flowing into the drawing plane, whereas a dot indicates a current flow of the winding out of the drawing plane. The winding includes the least one turn. The slots 1 to 18 for receiving the winding 20 are semi-open slots or open slots. To facilitate positioning of the winding 20 in the slots 22, whereby the slot number N = 1 to 18, the gap 25 has a width which is at least half the width W of the slot 22.

[0023] The winding 20 can be secured in the slots N by conventional processes, for example by encapsulation through casting or use of locking wedges, which are preferably mechanically affixed to the laminated core.

[0024] FIG. 2 shows a layout of a two-layer stator winding with a slot number N = 9. The winding 20 of this second embodiment has the same winding factors as the single layer winding of a stator with the slot number N = 18 slots.

